

Australian & New Zealand Distributor

OzLED (Aust) Pty Ltd


218 Leitchs Rd Brendale, QLD, 4500 Telephone (07) 3205 4355 Website: WWW.OZLED.COM.AU E-mail: sales@ozled.com.au

⚠ WARNING

This product contains high-powered LEDs. Avoid staring into light at close range or for excessive periods of time.

OZ41 - LED Warning Light Instruction Manual

Technical Specifications				
Dimensions	56mm x 46 mm x 29 mm			
Input Voltage	10-16 VDC			
Operating Temperature	- 40° to + 65°C			
Current Consumption	0.5A @ 12.8V			
LED Power	4 x 3W per LED			



Initial Setup to Power Supply:

- 1. Ensure the Power Supply is 12 VDC
- 2. Connect BLACK wire to GROUND
- 3. Connect RED wire to user-supplied switch. Connect the other side of the switch, through an 5A fuse, to the 12VDC +/- power supply.

Wiring Configuration								
Color	Function Description							
Red	Positive	Positive Power Input						
Black	Negative (Ground)	Negative Power Input (Ground)						
Blue	Pattern Change	Flash pattern selection. Make wire contact with POSITIVE for: 1. Less than 1 second for next pattern; 2. 1 to 3 seconds for previous pattern; 3. More than 3 seconds to return to pattern 1.						
Yellow	Synchronization	Synchronization mode for two or more modules. Mode of operation is as follows: 1. Select required flash pattern on each module 2. Disconnect the power 3. Join YELLOW wires of each module together 4. Reconnect the power						
Green	Dim	Connect to POSITIVE for HALF MODE.						

	Flash Patterns							
Description								
P1	Simultaneous Flash Quint Phase 1	75/min	P8	Simultaneous Flash Single Phase 2	375/min			
P2	Simultaneous Flash Quint Phase 2	75/min	Р9	All-In Quad x2 + All-In Single x4	75/min+150/min			
Р3	Simultaneous Flash Quad Phase 1	75/min	P10	Fast -> Slow (POP-Cycle)				
P4	Simultaneous Flash Quad Phase 2	75/min	P11	All-In Quad x2 + All-In Single x4 + POP-Cycle	75/min+150/min			
P5	Simultaneous Flash Single Phase 1	140/min	P12	Steady On				
P6	Simultaneous Flash Single Phase 2	140/min	P13	OFF				
P7	Simultaneous Flash Single Phase 1	375/min						