



Recess Mount



Features

- > New vehicle design integration
- > Single, Split, Dual and Tri-Color capability
- > 6, 9, 12 and 18 LED counts
- > Steady-burn white capability

Configurable Features

- > nFORCE is the only perimeter lighting product line on the market that can be specifically tailored to your unique requirements.

Visit www.soundoffsignal.com/product/nforce-recess-mount/ for an order form when ordering custom options and for additional information.

6 LED, Solid or Split Colors

#ENFSRS1(x)

9 LED, Solid Colors

#ENFSRS2(x)

12 LED, Solid or Dual Colors

#ENFSRS3(x)

18 LED, Tri Colors - Blue/Red/Amber or Blue/Red/White

#ENFSRS4(xxx)

9 LED, Solid Colors - Amber, Blue, Red or White, Xylex Lens and ECE R65 #ENFSRE2(x)

Replace (x) or (xxx) in the Order Number for Standard Color Selection

Solid Colors: A = ■ B = ■ R = ■ W = ■
 Dual Colors: D = ■ ■ E = ■ ■ F = ■ ■ J or JJ = ■ ■ Tri-Colors: BRA = ■ ■ ■ BRW = ■ ■ ■

Single

Solid Colors (x) = A, B, R or W
 6 LED Split Colors (x) = J
 9 LED Solid Colors (x) = A, B, R or W
 12 LED Dual Colors (x) = D, E, F or J
 18 LED Tri-Colors (xxx) = BRA (blue/red/amber) or BRW (blue/red/white)

Module LED Color Patterns

6 LED Solid: ■ ■ ■ ■ ■ ■
 6 LED Split: ■ ■ ■ ■ ■ ■
 9 LED Solid: ■ ■ ■ ■ ■ ■ ■ ■ ■
 12 LED Solid: ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■
 12 LED Dual: ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■
 18 LED Tri-Color: ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Technical Specifications

FLASH PATTERNS	12 Single color patterns, 14 Dual or 14 Tri-color patterns	
INPUT VOLTAGE	10-16 Vdc standard or 10-30 Vdc (custom order)	
CURRENT DRAW PER MODULE	10-16 VDC	10-30 VDC (custom order)
6 LED Single Color	< 1.0 Amp @ 12.8Vdc	< 0.6 Amps @ 25.6Vdc
6 LED Split Color	< 1.0 Amp @ 12.8Vdc	< 0.6 Amps @ 25.6Vdc
9 LED Single Color	< 1.5 Amps @ 12.8Vdc	< 0.9 Amps @ 25.6Vdc
12 LED Single Color	< 2.0 Amps @ 12.8Vdc	< 1.2 Amps @ 25.6Vdc
12 LED Split Color	< 1.0 Amp @ 12.8Vdc	< 0.6 Amps @ 25.6Vdc
18 LED Tri-Color	< 1.0 Amp @ 12.8Vdc	< 0.6 Amps @ 25.6Vdc
LIGHT SYNC	24	
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F	
DIMENSIONS	5.25" (13.34 cm) L x 2.25" (5.72 cm) H x 1.50 (3.8 cm) D	
CERTIFICATIONS	SAE J595, Class 1 certified; CA Title 13, Article 22 compliant; EMC 72/245/EEC certified; and ECE R65, Category X, Class 2 certified (ECE R65 can only be specified with 9 LED solid color)	
WARRANTY	Five-year	

