

nLINE

Running Light



48" Length Shown

36", Driver, Left Side Wire Exit	#ENL136(x)-L
36", Passenger, Right Side Wire Exit	#ENL136(x)-R
48", Driver, Left Side Wire Exit	#ENL148(x)-L
48", Passenger, Right Side Wire Exit	#ENL148(x)-R
60", Driver, Left Side Wire Exit	#ENL160(x)-L
60", Passenger, Right Side Wire Exit	#ENL160(x)-R
72", Driver, Left Side Wire Exit	#ENL172(x)-L
72", Passenger, Right Side Wire Exit	#ENL172(x)-R

Replace (x) in the Order Number for Color Selection

Solid Colors: A= ■ B= ■ R= ■ W= □

Dual/Split Colors: D= ■ □ E= ■ □ F= ■ □ J= ■ ■ K= ■ ■ M= ■ ■

Features

- > Light is sold per unit
- > Light can be surface mounted to any flat area on any type of vehicle
- > Prime applications include rocker panels, push bumpers, tailgates and headache racks
- > Distributes exceptional profile visibility to dangerous intersections
- > Compact extruded aluminum housing is visually inconspicuous and weather resistant
- > 19 inches of wire cable for hard wire installation



Technical Specifications

FLASH PATTERNS	10 flash patterns
LIGHT SYNC	6
INPUT VOLTAGE	10-16 Vdc
CURRENT DRAW	0.58 Amps @ 16 Vdc
OPERATING TEMPERATURE	-40° C to +65° C / -40° F to +149° F
DIMENSIONS	36" (91.4 cm) W 48" (121.9 cm) W 60" (152.4 cm) W 72" (182.9 cm) W .75" (1.9 cm) D (all lights)
MOUNTING	Surface mount
WARRANTY	Three-year