

BEACONS

4500 Series LED



Features

- > Lens with UV inhibitor prevents sun fade
- > Rated to last 20,000+ hours
- > Heavy duty cast aluminum base

Replace (x) and (xx's) in Order Number for Personalized Selections

#ELB45B(x)(xx)(xx)

(x) = Mounting Options: Flat/Pipe = **C**
Magnetic = **M**

(xx) = Height Options: Flat/Pipe, Low 4" Dome = **LØ**
Flat/Pipe, High 6" Dome = **HØ**
Magnetic Mount, Low 4" Dome = **L+**
Magnetic Mount, High 6" Dome = **H+**

(xx) = LED / Dome Color Options: Amber / Amber = **AA** Green / Green = **GG**
Amber / Clear = **AC** Red and Blue / Clear (low dome only) = **JC**
Amber and White / Clear = **FC** Red / Clear = **RC**
Blue / Blue = **BB** Red / Red = **RR**
Green / Clear = **GC** White / Clear = **WC**

ACCESSORIES Beacon not included.



branch guards

Branch Guard, 4" Height #PESB41BG4
Branch Guard, 6" Height (shown) #PESB41BG6



dust cover

Dust Cover, 4" Height #E36ØDC4
Dust Cover, 6" Height (shown) #E36ØDC6

Technical Specifications

FLASH PATTERNS	8 flash patterns
LED COUNT	12 LEDs
INPUT VOLTAGE	10-30 Vdc
CURRENT DRAW	1 Amp @ 12 Vdc, 0.5 Amps @ 24 Vdc
OPERATING TEMPERATURE	-40° C to 65° C
DIMENSIONS	4" Dome with base: 5" (12 cm) H, 6.3" (16 cm) base diameter 6" Dome with base: 6.8" (17 cm) H, 6.3" (16 cm) base diameter
MOUNTING	Magnetic or Flat/Pipe mount
CERTIFICATIONS	SAE J845 Class 1 certified
WARRANTY	Five-year