

BEACONS

4500 and 4200 Series LED



REPLACE (x) AND (xx) IN ORDER NUMBER FOR PERSONALIZED SELECTIONS

Product Number: #ELB(xx)B(x)(xx)(xx)

Certifications: 45 = Class 1 or 42 = Class 2

Mounting Options: C = Flat/Pipe or M = Magnetic

Height Options: L+ = Magnetic Mount, Low 4" Dome or H+ for 6" Dome | LØ = Flat/Pipe, Low 4" Dome or HØ for 6" Dome

LED Color/Dome Color Options:

- AA = Amber/Amber ● BB = Blue/Blue ● GG = Green/Green ● RR = Red/Red
- AC = Amber/Clear ● BC = Blue/Clear ● GC = Green/Clear ● RC = Red/Clear
- WA = White/Amber ● WC = White/Clear ● JC = Red/Blue / Clear dome

4500 Series Only: ● JJ = Red/Blue / Red/Blue dome (low dome only) ● FC = Amber/White / Clear dome

Features

- > Lens with UV inhibitor prevents sun fade
- > Rated to last 20,000+ hours
- > Heavy duty cast aluminum base
- > Same footprint as our 4000 Series Beacons



accessories

Branch Guard and Dust Cover (Beacon not included)



Branch Guards (6" shown)

4" Height #PESB41BG4

6" Height #PESB41BG6



Dust Cover

6" Height #E36ØDC6

TECHNICAL SPECIFICATIONS: 4500 and 4200 Series LED

FLASH PATTERNS	8 flash patterns
LED COUNT	4500: 12 LEDs and 4200: 4 LEDs
INPUT VOLTAGE	10-30 Vdc
CURRENT DRAW	1 Amp @ 12 Vdc, 0.5 Amps @ 24 Vdc
OPERATING TEMPERATURE	-40° C to 65° C
DIMENSIONS	4" Dome with base: 5" (12 cm) H, 6.3" (16 cm) base diameter 6" Dome with base: 6.8" (17 cm) H, 6.3" (16 cm) base diameter
MOUNTING	Magnetic or Flat/Pipe mount
CERTIFICATIONS	4500: SAE J845 Class 1 certified or 4200: SAE J845 Class 2 certified
WARRANTY	Five-year