

Emetion ead amps

Lumens Dual-Light™ U Lumens Spotlight Lumens Floodlight

Spot Low Flood High Spot High Flood Low Dua

\mathbf{H} Lumens Spotlight

Lumens White Floodlight

Lumens Red Floodlight

Lumens Green Floodlight









- Beam distance rated at 82/60 meters
- Dual brightness spotlight and multiple brightness/color floodlight modes
- Engineered polymer housing
- Powered by 3 AAA batteries (included)

These non-rechargeable multi-function headlamps each feature a multi-position tilt head design and include an elastic head strap with a non-slip lining. The top mounted dual switches provide high/low-brightness spotlight and high/low-brightness floodlight (4608), and high/lowbrightness spotlight and white/red/green floodlight (4610) operation. Additionally, the spotlight & white floodlight settings on the 4608 can be selected simultaneously for even greater functionality. Power comes from 3 AAA premium batteries (included).

VIGHTS



NSP-4608B





NSP-4610B









High/low-brightness spotlight

& white floodlight switch

NSP-4610B

Spotlight

Spot Loom

White Flood <

Red Flood < Reen Flood <



NSP-4610B

White/red/areen

floodlight

Red/green

floodlight switch

Multi-Function Headlamps



FEATURES

- CREE[®] LED technology 50,000 + hours LED life
- High/low-brightness spotlight high/low-brightness floodlight Dual-Light[™] (4608)
- High/low-brightness spotlight white/red/green floodlight (4610)
- Focused spotlight beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Colored floodlight for night vision preservation (4610)
- Dual-Light (spotlight & white floodlight mode at same time, 4608) for maximum versatility
- Engineered polymer housing
- Dual switches located on top of light
- Adjustable ratchet tilt head
- Non-slip elastic head strap
- Waterproof
- Impact & chemical resistant
- Powered by 3 premium AAA alkaline batteries (included)
- Limited Lifetime Warranty*



purchaser's lifetime. Warranty = rrought is warranted to be nee from detects in worknahaship and materials for the original purchaser's lifetime. The Limited Lifetime Warranty includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two (2) years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

- Lumens: high spotlight-100, low spotlight-60, high floodlight-90, low floodlight-50, dual-light-180
- Run-time: high spotlight-5 hrs, low spotlight-13.5 hrs, high floodlight-4.25 hrs, low floodlight-13.75 hrs, dual-light-2.5 hrs
- Beam distance: 82 meters
- Water rating: IP-X7
- Drop rating: 2 meters
- Width: 2.6in, height: 2.1in, depth: 1.8in, weight: 3.3oz
- 180 100 60 LUMENS LUMENS LUMENS 2h 30min 5h 13h 82m 77m 55m 775cd 1384cd 1506cd $(\bigcirc$ 2m

NSP-4608B SPECIFICATIONS

NSP-4610B SPECIFICATIONS

- Lumens: high spotlight-150, low spotlight-80, white floodlight-100, red floodlight-9, green floodlight-18,
- Run-time: high spotlight-4 hrs, low spotlight-8 hrs, white floodlight-4 hrs, red floodlight-25 hrs, green floodlight-22.5 hrs,
- Beam distance: 60 meters
- Water rating: IP-X7
- Drop rating: 2 meters
- Width: 2.6in, height: 2.1in, depth:1.8in, weight: 3.3oz

| | 1.11.11.11 | |
|--------------|-----------------------|---------------------|
| FL1 STANDARD | HIGH 150 LUMENS | LOW 80 LUMENS |
| \bigcirc | 4h | 8h |
| | 60m | 43m |
| | 1377cd | 667cd |
| 2m | | |
| 1m | | |