

E8EOSS4

EOS SQUARE Series

TECHNICAL SPECIFICATIONS

Flash Patterns	40
Voltage	10-30 VDC
Current Draw	1A @ 12.8VDC
LEDs	3Watt GEN3 High Intensity
IP Rating	IP67
Working Temperature	-40°C to + 50°C

The all new EOS Square warning light is designed to fit into locations where conventional long lights do not fit. They also allow for multiple lights to be mounted in close proximity.

8EVP have designed the light with an extremely low profile of only 10mm.

The EOS Square is available in red, blue, amber, green, white and any combination of these in a split colour configuration.

Flash patterns include the all new, industry first Eight EVP cruise-flash™. This unique flash pattern provides a background light output of 5% between flashes which means you obtain a continuous light output when the light is activated.



DESCRIPTION
EOS Square

PART NUMBER
E8EOSS4(X)



REPLACE (x) OR (xx) IN ORDER NUMBER FOR COLOUR SELECTION



E8EOSR4

EOS ROUND Series

TECHNICAL SPECIFICATIONS

Flash Patterns	40
Voltage	10-30 VDC
Current Draw	1A @ 12.8VDC
LEDs	3Watt GEN3 High Intensity
IP Rating	IP67
Working Temperature	-40°C to + 50°C

The all new EOS Round warning light is designed to fit into locations where conventional long lights do not fit, such as the bumper mouldings where optional fog lights may be fitted.

8EVP have designed the light with an extremely low profile of only 10mm.

The EOS Round is available in red, blue, amber green, white and any combination of these in a split colour configuration.

Flash patterns include the all new, industry first Eight EVP cruise-flash™. This unique flash pattern provides a background light output of 5% between flashes which means you obtain a continuous light output when the light is activated.



DESCRIPTION
EOS Round

PART NUMBER
E8EOSR4(X)



REPLACE (x) OR (xx) IN ORDER NUMBER FOR COLOUR SELECTION

