

DR SERIES DOUBLE ROW LIGHTBARS



COLOUR TEMPERATURE: 5700 KELVIN

SPECIFICATIONS

SKU	MODEL	LUMEN OUTPUT	BEAM DISTANCE	POWER	LED CHIPS	CURRENT DRAW	DIMENSION A x B x C
B6D660C	6 INCH	1652 Lumens	1 lux @ 362m	60WATT	12x5w OSRAM	1.5A @ 12vdc	150mm x 72mm x 49mm
B6D10100C	10 INCH	3931 Lumens	1 lux @ 451m	120WATT	20x5w OSRAM	3.7A @ 12vdc	250mm x 72mm x 49mm
B6D20200C	20 INCH	7014 Lumens	1 lux @ 666m	200WATT	40x5w OSRAM	7.6A @ 12vdc	510mm x 72mm x 49mm
B6D30300C	30 INCH	9994 Lumens	1 lux @ 785m	300WATT	60x5w OSRAM	12.3A @ 12vdc	812mm x 72mm x 49mm
B6D40400C	40 INCH	13,146 Lumens	1 lux @ 882m	400WATT	120x5w OSRAM	15.9A @ 12vdc	1066mm x 72mm x 49mm
B6D50500C	50 INCH	15,783 Lumens	1 lux @ 992m	500WATT	200x5w OSRAM	21.1A @ 12vdc	1320mm x 72mm x 49mm

SHARED SPECS

LED POWER	5W LED Chips
LED MANUFACTURER	Genuine OSRAM®
BEAM PATTERN	Combination Spot & Flood
HOUSING MATERIAL	Diecast Aluminum
LENS MATERIAL	GE Lexan Polycarbonate
MOUNTING BRACKET	Side Mount Brackets
OPERATING VOLTAGE	10-30V DC
COLOUR TEMPERATURE	5,700K
LED LIFESPAN	50,000 hours
CERTIFICATIONS	CE, RoHS, C-Tick

