

LI-ION RECHARGEABLE

INTEGRITAS™ INTRINSICALLY SAFE LANTERN

XPR-5582RX  
XPR-5582GX

**NIGHTSTICK**®  
Life Depends on Light™



**1750**

**POWERFUL LUMENS**

INCLUDING HIGH & LOW

180° DOWNWARD ROTATION



**Rear green safety lights** provide visibility in smoke filled applications



**Carry strap with seat belt style buckle** for additional hands-free use



**Convenient locking snap-in charger** included




Dustproof/Waterproof (IP-67) and chemical/heat resistant for any environment




AVAILABLE IN MULTIPLE COLORS

FL 1 STANDARD	HIGH	LOW
	1750 LUMENS	600 LUMENS
	5h	11h
	552m	325m
	81250cd	27083cd



**1750 LUMENS**



1-800-233-2155 · 1-469-326-9400 · [nightstick.com](http://nightstick.com)

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

**INTEGRITAS™****LANTERN****LI-ION RECHARGEABLE****ITEM NUMBER/UPC**

XPR-5582RX (Red), UPC# 0 17398 806824  
 XPR-5582GX (Green), UPC# 0 17398 807029

**MARKET APPLICATIONS**

Hazardous work environments, fire, rescue, industrial and automotive

**CERTIFICATIONS**

- cETLus, CE, Meets requirements of NFPA-1971-8.6 (2013), Charger meets requirements of NFPA-1901 (2009) Mounted in any Position  
 - US Patent 9,713,217

**CASE MATERIAL**

- Glass filled nylon polymer

**LUMENS/RUNTIME****FLASHLIGHT**

- HIGH: 1750L, 5 hrs. runtime  
 - LOW: 600L, 11 hrs. runtime

**CANDELA****FLASHLIGHT**

- HIGH: 81,250  
 - LOW: 27,083

**BEAM DISTANCE****FLASHLIGHT**

- HIGH: 552m  
 - LOW: 325m

**WATER RATING**

- IP-67 (dustproof and waterproof)

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 7.54 in / 19.2 cm  
 - WIDTH: 4.26 in / 10.8 cm  
 - DEPTH: 5.83 in / 14.8 cm  
 - WEIGHT: 2 lbs. 11 oz. / 1219 g

**BATTERY**






- Rechargeable Li-ion battery pack

**WARRANTY**

- Limited lifetime warranty

**WHAT'S INCLUDED**

- Lantern  
 - Li-ion rechargeable battery pack  
 - Locking snap-in charger (5582-CHGR1)  
 - AC & DC power supply  
 - Removable shoulder strap  
 - Instruction manual

FL 1 STANDARD	HIGH	LOW
	<b>1750 LUMENS</b>	<b>600 LUMENS</b>
	<b>5h</b>	<b>11h</b>
	<b>552m</b>	<b>325m</b>
	<b>81250cd</b>	<b>27083cd</b>
	<b>2m</b> <b>1m</b>	



**Bayco Products, Inc. XPR-5582**  
 640 S. Sanden Blvd., Wylie, TX 75098

ID 4003544  
 INTRINSICALLY SAFE  
 SECURITE INTRINSEQUE

CLASS I DIV 2 GRPS A-D T3  
 CLASS II & III DIV 2 GRPS F-G T135°C  
 CLASS I ZONE 2 Group IIC T3  
 -20°C ≤ Tamb ≤ +40°C  
 3.7V/Cell 5582-BATT



WARNING: Risk of ignition - Do not open in a hazardous area.  
 AVERTISSEMENT: Ne pas ouvrir dans une zone dangereuse.  
 WARNING: Risk of ignition - Do not charge batteries in a hazardous area.  
 AVERTISSEMENT: Danger d'inflammation - Ne pas charger les piles dans une zone dangereuse.

**CERTIFIED**



AVAILABLE IN MULTIPLE COLORS