



bolt LED Lighting

Bolt is an extremely compact line of single and dual color LED perimeter lights.

Bolt's design and mounting options allow the light to be integrated nearly anywhere on a vehicle.



Quick and Stud Mounts



Screw Mount

Quick Mount, Black Housing

- 6 LED, Single color
- 8 LED, Single color
- 12 LED, Dual color

- EBTS2QMS2(x)**
- EBTS2QMS3(x)**
- EBTS2QMS4(x)**

Stud Mount, Black Housing

- 6 LED, Single color
- 8 LED, Single color
- 12 LED, Dual color

- EBTS2STS2(x)**
- EBTS2STS3(x)**
- EBTS2STS4(x)**

Screw Mount, Black Housing

- 6 LED, Single color
- 8 LED, Single color
- 12 LED, Dual color

- EBTS2SMS2(x)**
- EBTS2SMS3(x)**
- EBTS2SMS4(x)**

Replace (x) in the Order Number for Standard Color Selection

- 6 or 8 LED Single Colors: A = ● (Yellow) B = ● (Blue) R = ● (Red) W = ● (White)
 12 LED Dual Colors: D = ● (Red) ● (White) E = ● (Blue) ● (White) F = ● (Yellow) ● (White) J = ● (Red) ● (Blue)

Quick Mount



Installs with 3M VHB adhesive
 No exposed fasteners
 VHB seal light to vehicle

Stud Mount



Installs with threaded studs and nuts
 No exposed fasteners
 Three holes drilled into vehicle

Screw Mount



Installs with two screws
 Screws are exposed after installation
 Three holes drilled into vehicle

Features

- Thin, narrow LED light, fits almost anywhere
- Ability to integrate visually into today's vehicles
- Single and Dual LED colors options
- Durable Polycarbonate lens

Module LED Color Patterns



For configured products, bracket accessories and technical specifications, refer to the back of this flyer.



bolt PRODUCTS CAN BE CONFIGURED to meet your needs.

CONFIGURED FEATURES

Single green LED color or combined with other available colors
 Amber LED color combined with red, blue and white LED colors
 White LED color combined with red or blue LED colors

CONFIGURED PART NUMBERS

Quick Mount
EBTC2QMS26 LED
EBTC2QMS38 LED
EBTC2QMS412 LED

Stud Mount
EBTC2STS26 LED
EBTC2STS38 LED
EBTC2STS412 LED

Screw Mount
EBTC2SMS26 LED
EBTC2SMS38 LED
EBTC2SMS412 LED

CONFIGURED COLOR CODES

Single Color Codes

AmberA
 Blue.....B
 GreenG
 Red.....R
 White.....W

Dual Color Codes

Red/White.....D Red/Amber.....K
 Blue/White.....E Red/GreenL
 Amber/WhiteF Blue/Amber.....M
 Green/White.....H Blue/GreenN
 Red/BlueJ Green/Amber.....P

Bolt Mounting Accessories

QUICK CLIP
 Use with Quick Mount Light

PMP2BKQCLP



90 DEGREE DECK/GRILLE
 Adjustable Bracket Kit

PBT2BKDGAJ



90 DEGREE EDGE CLIP
 Bracket Kit

PBT2BKEDGE



35 Degree Wedge Assembly for the Quick Mount

Bolt light is sold separately.

4 Inch Wedge Assembly, Black **PMP2WDG35B**



35 Degree Wedge



Technical Specifications

INPUT VOLTAGE RANGE	10-30 Vdc
CURRENT DRAW	< 1.0 Amps @ 12.8Vdc, < 0.5 Amps @ 25.6 Vdc
LIGHT SYNC	24 single lighthoods
FLASH PATTERNS	12 Single or 14 Dual
OPERATING TEMPERATURE	-40° C to +65° C
DIMENSIONS	<p>Quick Length: 4.25"(10.8cm) Height: 1.10" (2.8cm) Depth: .50" (1.27cm) (from mounting surface)</p> <p>Stud Length: 4.25"(10.8cm) Height: 1.10" (2.8cm) Depth: .44" (1.12cm) (from mounting surface)</p> <p>*not including gasket</p> <p>Screw Length: 4.72"(12.0cm) Height: 1.10" (2.8cm) Depth: .44" (1.12cm) (from mounting surface)</p> <p>*not including gasket</p>
CERTIFICATIONS	SAE J595 and J845 Class 1 certified and CA Title 13
WARRANTY	Five-year