



## Features

- > LED 'hide away' insert elevates safety lighting with interchangeable lenses that tailor the light output to complement your mounting application
- > 2 additional lenses available for customized light output
- > Retrofits with existing 1" strobe tube cutouts in headlight, taillight or corner lights in all types of commercial vehicles
- > Optional cruise mode reduces light output to 20% brightness
- > Use with optional bezels to surface mount to any flat area on the vehicle body for additional lighting anywhere

## LED Inserts



### Screw-In LED Inserts

10' Cable Length, 10-16 Vdc

#ELUC2SØ1Ø(x)

10' Cable Length, 10-30 Vdc

#ELUC2HØ1Ø(x)

Includes extreme angle lens, inline flasher and cable for hardwire installation

10' Cable Length with Quick Connect

#ELUCCSØ1Ø(x)

25' Cable Length

#ELUC2SØ25(x)

### Replace (x) n the Order Number for Color Selection

Solid Colors: A= ■ B= ■ G= ■ R= ■ W= □  
 Dual/Split Colors: D= ■ □ E= ■ □ F= ■ □ H= ■ □ J= ■ ■ K= ■ ■ L= ■ ■ M= ■ ■ N= ■ ■ P= ■ ■

## Technical Specifications

FLASH PATTERNS	33 flash patterns
LIGHT SYNC	4
LED COUNT	6 LEDs
INPUT VOLTAGE	10-16 Vdc or 10-30 Vdc
CURRENT DRAW	< 1.0 Amp (flash pattern dependent) @ 12.8 Vdc
OPERATING TEMPERATURE	-40° C to +65° C
DIMENSIONS	Insert: 1.5" (3.8 cm) Diameter x 0.9" (2.3 cm) H Bezel: 2.2" (5.6 cm) L x 1.65" (4.2 cm) H x 0.63" (1.6 cm) D
MOUNTING	Headlight/Taillight mount into 1" Diameter cutouts Screw-In Surface mount with optional bezel Bezel mounts on 1.89" (4.8 cm) centers Twist-In or Push-In options are also available
CERTIFICATIONS	EMC, ECE R10 (10-16 Vdc only)
WARRANTY	Five-year



## LED Inserts

[continued]

### ACCESSORIES Light not included. bezels

- a. White
- b. Black
- c. Chrome

#PLUC2HSW  
 #PLUC2HSB  
 #PLUC2HSC

Includes mounting gasket and hardware



### additional lens

- a. Extreme Angle
- b. Horizontal
- c. Vertical

#PLUC2LN1E  
 #PLUC2LN1H  
 #PLUC2LN1V



### kits

- Push-In
- Twist-In

#PLUCPGR1  
 #PLUCTCL1